

Faculty Mission: Enable 49 ML & AI Solutions

That 1.4 Billion People Are Waiting For

Where Intelligent Software Meets Designed-and-Built-in-India Hardware

Appendix A1: Agriculture & Grain Solutions

AG-1 to AG-6 (Agriculture) · GR-1 to GR-5 (Grain & Food Stock) · 11 Solutions

Combined Annual Impact: ₹2,91,000 Crore · 140M Farming Households · 600,000 Villages

For: ECE & CSE Faculty · Final Year Students · ME Research Students · HODs

Part of Document Set: Appendix A (A1–A6) | Full cross-reference index → Appendix A6

Table of Contents

Contents

Table of Contents	2
How to Use This Document	4
Domain Overview — Agriculture & Grain	5
Appendix A-1 — Agriculture: 6 Solutions	6
AG-1: Key Government APIs & Links	7
AG-1: Engineering Notes.....	7
AG-2: Key Government APIs & Links	8
AG-2: Engineering Notes.....	9
AG-3: Key Government APIs & Links	10
AG-3: Engineering Notes.....	11
AG-4: Key Government APIs & Links	12
AG-4: Engineering Notes.....	13
AG-5: Key Government APIs & Links	14
AG-5: Sensor Integrity Deep Note	15
AG-6: Key Government APIs & Links	16
AG-6: Engineering Notes.....	17
Agriculture Domain Summary — The Six Solution Arc.....	18
Appendix A-2 — Grain & Food Stock: 5 Solutions	19
GR-1: Key Government APIs & Links	20
GR-1: Engineering Notes.....	20
GR-2: Key Government APIs & Links	21
GR-2: The Open Innovation Note	22
GR-3: Key Government APIs & Links	23
GR-3: Engineering Notes.....	24
GR-4: Key Government APIs & Links	25
GR-4: Engineering Notes — Legal Metrology is Not Optional	26
GR-5: Key Government APIs & Links	27
GR-5: Engineering Notes.....	28
Grain & Food Stock Domain Summary — The Five-Solution Chain	29
Shared Engineering Principles — Agriculture & Grain Domain	30
1. Soil and Grain Contact Sensor Materials.....	30
2. AC Excitation — Mandatory for All Electrochemical Sensors	30
3. NABL Calibration vs NABL Accreditation — The Difference That Matters	31
4. Legal Metrology — India's Most Misunderstood Certification.....	31
5. LoRa India Band — The Most Common Implementation Error	32

How to Use This Document

This is Appendix A1 — the detailed specification reference for Agriculture and Grain solutions. Every solution is reproduced exactly as built in the original design session: every hardware dimension, every sensor integrity warning, every government API link, and every POC vs engineering target distinction.

This appendix is not for reading in one sitting.
It is a reference map.

Use it to:

- Identify final year project topics relevant to your department
- Specify hardware and software requirements before approving a project
- Connect students to government APIs relevant to their solution
- Argue for lab equipment based on specific solution requirements
- Build a department research agenda around real Indian problems

Each solution is specified across eight dimensions:

- Scale — how big is this problem in India?
- Impact — what changes if this is solved?
- Hardware needed — what must be designed and built?
- Software needed — what must be written and integrated?
- Why local — why cannot this be imported or outsourced?
- Sensor integrity note — the engineering discipline that makes data trustworthy
- POC entry point — the logical check (not engineering check)
- Engineering target — what a deployable product looks like

THE POC HONESTY PRINCIPLE — applies to every specification in this document

*Every hardware specification below describes the engineering-grade product requirement.
Not the POC dev board.*

*The POC entry point listed for each solution answers: 'Does my logic work?'
The engineering target answers: 'Can this be deployed in India legally, reliably and at scale?'*

*These are two different questions.
Only the engineering target produces a product.
The POC produces a demo.*

*Appendix C1: Engineering Integrity explains every dimension of this distinction.
Appendix C2: Sensor Integrity explains why every sensor integrity note below is non-negotiable.*

Domain Overview — Agriculture & Grain

Domain	Solutions	Annual Impact	Primary Sensor Challenge	Primary Software Challenge
Agriculture	6 (AG-1 to AG-6)	₹2,30,000 Cr	Soil chemistry — SS316L + AC excitation + NABL calibration	India-specific ML + 12-language voice + offline-first
Grain Management	5 (GR-1 to GR-5)	₹61,000 Cr	Grain probe + CO ₂ NDIR + Legal Metrology load cells	FCI FIMS + PDS APIs + state-by-state integration

The agriculture domain is where India's IoT engineering opportunity is most visible and most neglected simultaneously. 140 million farming households produce food for 1.4 billion people. Not one of them has access to a calibrated, trustworthy, India-specific soil intelligence system at a price they can afford. That system does not exist yet. It must be built. By engineers trained in India's classrooms.

Appendix A-1 — Agriculture: 6 Solutions

Agriculture — 6 Solutions | 140 Million Farming Households Waiting

India has 140 million farming households, 600,000 villages, and 180 million hectares of cultivated land. It wastes enough food every year to feed 100 million additional people. The farmer who grew it has no idea why his crop failed, why his irrigation wasted 80% of the water, or when his tractor was about to break down. Every one of those failures is an IoT engineering problem with a known solution.

AG-1 Soil & Crop Intelligence Network

Agriculture · Year 2–3 · ECE + CSE

Dimension	Detail
Scale	140M farming households, 600,000 villages, 180M hectares cultivated land
Impact	30% water saving, 20% yield increase, reduce ₹1.5L cr annual crop loss
Hardware needed	Soil NPK sensor — stainless steel 316L electrodes, AC excited at 1–10 kHz; soil moisture — capacitive, coated against soil chemistry; solar-powered node — MPPT + LiPo; LoRa gateway — weatherproof IP67 enclosure; all designed for 45°C+ ambient
Software needed	Edge ML crop advisory on STM32U5; PM-KISAN API integration; e-NAM price feed; regional language voice advisory — 12 Indian languages minimum; offline-first architecture
Why local	Indian soil profiles — Vertisols of Deccan, Alluvials of Indo-Gangetic plain — require India-specific sensor calibration. Sub-₹800 BOM target impossible with imported sensors. No global vendor will calibrate for Marathwada soil chemistry
Sensor integrity note	⚠ Soil moisture sensor must use AC excitation — DC causes electrolysis. Calibration must be traceable to NABL reference. Lifetime: 6–18 months in field conditions. Dashboard must show calibration status
POC entry point	ESP32 + capacitive soil moisture sensor + ThingSpeak — logical check only
Engineering target	STM32U5 + custom 4-layer PCB + NABL-calibrated sensor + LoRa STM32WL + IP67 enclosure

AG-1: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
PM-KISAN	pmkisan.gov.in	Farmer identity verification, benefit linkage, direct payment trigger
e-NAM	enam.gov.in	Real-time mandi price feed, advisory calibration against market price
ICAR Soil Data	icar.org.in	India-specific soil profiles, crop advisory datasets, agro-climatic zone data
Digital Agriculture Mission	agricoop.gov.in	National farmer registry (Agri Stack), crop monitoring integration
VDAS — Village Digital Advisor	dahd.gov.in	Village-level advisory service integration

AG-1: Engineering Notes

Soil moisture sensor — DC excitation causes electrolysis within days.

Ion migration deposits minerals on probe electrodes.

Mineral deposit permanently shifts the electrical characteristics.

Reading drifts. The dashboard shows confident numbers. The numbers mean nothing.

AC excitation at 1–10 kHz is mandatory. There is no alternative.

Hardware progression: ESP32 + DHT22 (Year 1 logical check) → STM32U5 + capacitive sensor on 4-layer PCB (Year 2) → NABL-calibrated NPK probe + LoRa STM32WL + IP67 (Year 3) → full soil intelligence node with crop advisory ML (Year 4)

LoRa frequency note: India band is 865–867 MHz. NOT 868 MHz (European default). Configure in firmware before field deployment.

Battery life target: 1 year minimum on 3.7V/5000mAh LiPo with solar top-up. Verify with Nordic PPK2 before field deployment.

Enclosure note: Carbon-black ABS absorbs RF — use natural/white ABS or polycarbonate near antenna. IP67 minimum for Indian field conditions (monsoon + dust + 45°C).

AG-2 Cold Chain for Perishables

Agriculture · Year 3–4 · ECE + CSE

Dimension	Detail
Scale	40% fruit/veg wasted = ₹92,000 cr loss annually; 7,000+ APMC mandis unmonitored
Impact	25–30% post-harvest loss reduction; ₹23,000 cr saved annually
Hardware needed	Temperature + humidity logger — $\pm 0.1^{\circ}\text{C}$ accuracy, NABL calibrated; GPS tracker; NFC smart seal — tamper evident; ruggedised packaging for Indian truck vibration profile; LiPo + NB-IoT; IP67
Software needed	Spoilage prediction ML — trained on Indian route + climate data; ONDC integration; e-NAM marketplace API; real-time dashboard; driver SMS alert in regional language
Why local	Indian cold chain routes — Nashik to Chennai, Azadpur mandi to Bangalore — not mapped in any global platform. ONDC integration requires India-registered entity
Sensor integrity note	⚠ Temperature sensor must be NABL calibrated. Calibration certificate must travel with consignment. Dashboard must show calibration status at time of each reading
POC entry point	ESP32 + DS18B20 temperature sensor + ThingSpeak — logical check only
Engineering target	Custom PCB + NABL-calibrated PT100 RTD + NB-IoT modem + GPS + tamper-evident NFC seal + IP67 enclosure

AG-2: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
ONDC	ondc.org	Open Network for Digital Commerce — seller API, logistics integration
e-NAM	enam.gov.in	APMC mandi integration, commodity price feed, buyer-seller matching
NHB Cold Chain	nhb.gov.in	National Horticulture Board cold chain infrastructure data
WDRA	wdra.gov.in	Warehouse Development & Regulatory Authority — digital receipts
APEDA	apeda.gov.in	Agricultural & Processed Food Export — export cold chain standards

AG-2: Engineering Notes

PT100 RTD vs DS18B20 — the engineering difference:

DS18B20: $\pm 0.5^{\circ}\text{C}$ accuracy, no NABL calibration available, no certificate. Year 1 logical check only.

PT100 RTD: $\pm 0.1^{\circ}\text{C}$ accuracy, NABL calibration available, certificate issued. Engineering-grade.

The $\pm 0.4^{\circ}\text{C}$ difference is not just a number. It is whether a consignment is accepted or rejected at destination.

A consignment declared 'within $0-4^{\circ}\text{C}$ ' by an uncalibrated sensor may have reached 4.4°C .

That consignment is legally compliant on paper and potentially unsafe in reality.

NB-IoT note: India Band 5 (850 MHz) and Band 28 (700 MHz). Verify carrier support before designing modem selection.

NB-IoT in refrigerated trucks: metal body creates Faraday cage — external antenna via bulkhead connector mandatory.

AG-3 Drip Irrigation Automation

Agriculture · Year 2–3 · ECE + CSE

Dimension	Detail
Scale	70M hectares irrigated land; 80% uses flood irrigation — massive water waste
Impact	50% water saving vs flood irrigation; PM-KUSUM scheme linkage for solar power
Hardware needed	Soil moisture sensor — AC excited, coated electrodes; flow meter — ultrasonic, no moving parts; solenoid valve controller; solar MPPT node; LoRa mesh — field coverage 2–5 km
Software needed	ET-based irrigation scheduling ML — evapotranspiration model for Indian crops; PM-KUSUM API; state water board integration; farmer mobile app — Marathi, Telugu, Kannada, Tamil
Why local	State-specific crop calendars, local water table data, PM-KUSUM scheme — entirely India-specific
Sensor integrity note	⚠ Flow meter must be calibrated against volumetric reference. Soil moisture AC excitation mandatory. Calibration drift monitoring in firmware
POC entry point	Arduino + soil moisture sensor + relay module + Blynk — logical check only
Engineering target	STM32U5 + 4-layer PCB + ultrasonic flow meter + solenoid driver + LoRa STM32WL

AG-3: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
PM-KUSUM	mnre.gov.in/pm-kusum	Solar pump scheme, subsidy calculation, beneficiary registration
ICAR Crop Water	icar.org.in	Crop water requirement data, evapotranspiration reference values
FAO ET Calculator	fao.org/land-water/databases-and-software/eto-calculator	Reference evapotranspiration — Penman-Monteith method for Indian crops
PMKSY	pmksy.gov.in	Pradhan Mantri Krishi Sinchayee Yojana — irrigation scheme integration
State Water Boards	Various state portals	Local water table data, aquifer depletion alerts (varies by state)

AG-3: Engineering Notes

Ultrasonic flow meter vs impeller (turbine) type:

Impeller: moving parts, clogs with sediment in Indian irrigation water. Fails within 3–6 months.

Ultrasonic: no moving parts, no clogging, calibrated. Engineering choice.

Solenoid valve note: India 12V DC latching solenoid saves 95% power vs non-latching. Critical for solar battery life.

Latching solenoid requires pulse to open and pulse to close — firmware must handle both.

ET model note: Penman-Monteith equation is the FAO standard. Requires: temperature, humidity, wind speed, solar radiation.

Indian crop-specific Kc (crop coefficient) values are published by ICAR for major crops.

Use Indian Kc values — not FAO generic values — for reliable irrigation scheduling.

AG-4 Livestock Health Monitoring

Agriculture · Year 3–4 · ECE + CSE

Dimension	Detail
Scale	535M livestock — world's largest herd; ₹20,000 cr annual disease loss
Impact	Early disease detection, estrus detection — 40% reduction in livestock mortality
Hardware needed	Ear-tag sensor — temp + rumination + GPS; coin-cell powered; nRF5340 BLE; IP68 rated for animal contact; body-safe materials — no toxic coatings
Software needed	Rumination pattern ML — estrus, fever, illness detection; INAPH (National Animal Disease Reporting) integration; NDDDB API; farmer WhatsApp alert
Why local	Indian cattle breeds — Gir, Sahiwal, Murrah buffalo — different rumination patterns from Holstein. INAPH is India-specific government platform
Sensor integrity note	⚠ Temperature sensor on animal body — must be body-safe, non-toxic. Calibration must account for fur insulation effect. Lifetime: ear-tag must survive 2+ years of animal activity
POC entry point	Arduino Nano 33 BLE Sense + Edge Impulse motion classification — logical check only
Engineering target	Custom nRF5340 PCB + body-safe enclosure + BLE + LoRa gateway + INAPH API

AG-4: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
INAPH	inaph.nddb.coop	National Animal Disease Reporting — disease event logging, herd health tracking
NDDDB	nddb.coop	National Dairy Development Board — cattle registry, breed data
e-Pashuhaat	epashuhaat.gov.in	National livestock marketplace — cattle valuation, transaction records
DADF	dahd.gov.in	Department of Animal Husbandry — scheme registration, subsidy access
Edge Impulse	edgeimpulse.com	TinyML platform for rumination + activity classification on nRF5340

AG-4: Engineering Notes

Indian vs Western cattle breed difference — why global ML models fail:

Holstein cow: rumination 7–9 hours/day, characteristic jaw movement frequency ~1.1 Hz

Gir / Sahiwal: rumination 6–8 hours/day, different jaw frequency and rhythm signature

Murrah buffalo: very different rumination pattern — slower, longer bolus re-chewing

Training an ML model on Holstein data to detect Murrah estrus will produce garbage output.

Coin cell power budget for ear-tag:

CR2450 cell: 620 mAh at 3V

nRF5340 in sleep: ~2 μ A; active BLE: ~5 mA; IMU active: ~0.5 mA

Duty cycle: 1s IMU sample, 30s BLE burst, rest in sleep

Expected lifetime: 18–24 months — verify with Nordic PPK2

Body-safe materials: ABS plastic is fine. Carbon-black ABS (black colour) contains carbon black pigment — verify RoHS compliance. No lead, cadmium, hexavalent chromium in enclosure near animal.

AG-5 Aquaculture & Fishery Monitoring

Agriculture · Year 3–4 · ECE + CSE

Dimension	Detail
Scale	28M fishermen; ₹2.3L cr fishery GDP; 40% fish mortality from poor water quality
Impact	Real-time water quality → 40% mortality reduction; better catch forecasting
Hardware needed	Multi-parameter water quality probe — DO, pH, ammonia, temperature, salinity; buoy-mounted node; marine-grade SS316L housing; solar + LiPo; LoRa to shore
Software needed	Water quality anomaly ML; ocean current integration; PMMSY scheme API; weather forecast integration; fisherman mobile app — Tamil, Malayalam, Telugu, Odia
Why local	Indian coastal water profiles — Bay of Bengal, Arabian Sea — different from global models. PMMSY is India-specific scheme. Local fish species behaviour
Sensor integrity note	⚠ DO sensor membrane degrades in saline water — replacement schedule mandatory. pH electrode requires daily buffer calibration in marine environment. All calibrations logged on dashboard
POC entry point	ESP32 + pH sensor module + DO sensor + ThingSpeak — logical check only
Engineering target	STM32H7 + multi-channel ADC + marine-grade SS316L housing + LoRa + solar MPPT

AG-5: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
PMMSY	dof.gov.in/pmmsy	Pradhan Mantri Matsya Sampada Yojana — scheme registration, subsidy access
INCOIS Fishery	incois.gov.in	Ocean current data, fish potential zones, weather alerts
MPEDA	mpeda.gov.in	Marine Products Export — quality certification, traceability
NFDB	nfdb.gov.in	National Fisheries Development Board — infrastructure support
IMD Ocean Met	moes.gov.in	Sea surface temperature, wave height, weather forecast for coastal areas

AG-5: Sensor Integrity Deep Note

DO (Dissolved Oxygen) sensor — the most demanding sensor in this system:

Galvanic DO probe: silver cathode reduces oxygen to hydroxide. Membrane isolates electrolyte from sample.

Saline water: salt ions accelerate membrane degradation. Replace membrane every 1–3 months in marine environment.

Temperature compensation mandatory — DO solubility is strongly temperature-dependent (14.6 mg/L at 0°C → 7.6 mg/L at 30°C).

Calibration: 100% air saturation method OR Winkler titration method against certified reference.

pH electrode in marine environment:

Junction potential drift due to high ionic strength of seawater — significant calibration offset vs freshwater.

Use seawater-specific calibration buffers, not standard pH 4/7/10 buffers designed for freshwater.

Calibration frequency: daily in marine deployment. Firmware must log and alert on calibration overdue.

AG-6 Farm Equipment Telematics

Agriculture · Year 3–4 · ECE + CSE

Dimension	Detail
Scale	3M tractors, 600K harvesters; ₹1,200 cr annual breakdown loss for farmers
Impact	25% fuel saving; predictive maintenance — prevent 70% of unplanned breakdowns
Hardware needed	GPS + OBD adapter — Indian tractor OBD port mapping; engine vibration sensor; fuel flow sensor; 4G modem; IP54 cab-mounted enclosure — dust and vibration rated
Software needed	Engine anomaly ML — trained on Indian tractor models (Mahindra, TAFE, Sonalika, Eicher); CHC (Custom Hiring Centre) portal API; fuel theft detection algorithm; fleet dashboard
Why local	Indian tractor models not in any global OBD database. CHC portal is India-specific. Tractor engine failure signatures unique to Indian field conditions
Sensor integrity note	⚠ Vibration sensor must be calibrated per ISO 10816. Fuel flow meter requires volumetric calibration. Calibration must survive tractor vibration profile
POC entry point	ESP32 + OBD-II module + GPS + ThingSpeak — logical check only
Engineering target	Custom PCB + vibration sensor + fuel flow meter + 4G modem + GPS + IP54 enclosure

AG-6: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
CHC Portal	chcfarm.in	Custom Hiring Centre — farm machinery booking, utilisation tracking
ICAR Mechanisation	icar.org.in	Farm mechanisation data, crop-machine matching guidelines
VAHAN	vahan.parivahan.gov.in	Vehicle registration integration for commercial farm equipment
SMAM Scheme	agrimachinery.nic.in	Sub-Mission on Agricultural Mechanisation — subsidy integration
PM-KISAN	pmkisan.gov.in	Farmer ID linkage for personalised fleet advisory

AG-6: Engineering Notes

Indian tractor OBD reality: Most pre-2015 Indian tractors have NO OBD port.

Solution: Retrofit CAN bus tap directly on the engine controller harness.

This requires knowledge of the specific tractor model's CAN IDs — which are not publicly documented.

The innovation gap: India needs an open-source Indian tractor CAN ID database.

The student who builds it creates a foundational resource for all future Indian agri-IoT.

ISO 10816 vibration calibration: measures vibration velocity in mm/s.

Zone A (new machinery): < 2.3 mm/s RMS

Zone B (acceptable): 2.3 – 4.5 mm/s RMS

Zone C (alarm): 4.5 – 7.1 mm/s RMS

Zone D (fault): > 7.1 mm/s RMS

Calibration: MEMS accelerometer must be calibrated against certified shaker table at 3 axis.

Fuel theft detection: Turbine flow meter + capacitive fuel level sensor cross-validation.

Sudden fuel level drop not accompanied by engine-on and flow meter reading = theft event.

GPS location at time of event logged automatically.

Agriculture Domain Summary — The Six Solution Arc

The six agriculture solutions form a complete arc from soil to shelf — soil intelligence (AG-1) → post-harvest cold chain (AG-2) → precision irrigation (AG-3) → livestock health (AG-4) → aquaculture (AG-5) → equipment telematics (AG-6). Each can be built independently. Together they form a complete digital farm management system for India.

Solution	Year	Team	POC (Logical Check)	Engineering Target	Impact
AG-1 Soil Intelligence	2–3	ECE+CSE	ESP32 + soil sensor + ThingSpeak	STM32U5 + NABL sensor + LoRa + IP67	₹1,50,000 Cr
AG-2 Cold Chain	3–4	ECE+CSE	ESP32 + DS18B20 + ThingSpeak	Custom PCB + PT100 RTD + NB-IoT + IP67	₹23,000 Cr
AG-3 Drip Irrigation	2–3	ECE+CSE	Arduino + soil sensor + relay + Blynk	STM32U5 + ultrasonic flow + LoRa	₹30,000 Cr
AG-4 Livestock Health	3–4	ECE+CSE	Nano 33 BLE + Edge Impulse motion	Custom nRF5340 + ear-tag + LoRa + INAPH API	₹20,000 Cr
AG-5 Aquaculture	3–4	ECE+CSE	ESP32 + pH + DO + ThingSpeak	STM32H7 + marine SS316L sonde + LoRa	₹15,000 Cr
AG-6 Farm Telematics	3–4	ECE+CSE	ESP32 + OBD + GPS + ThingSpeak	Custom PCB + vibration + flow + 4G + IP54	₹12,000 Cr

Appendix A-2 — Grain & Food Stock: 5 Solutions

| Grain & Food Stock — 5 Solutions | ₹92,000 Crore Lost Every Year

India stores 80 million tonnes of grain annually across 150,000+ Fair Price Shops, 2,300 silos, and 700+ FCI depots. It loses ₹92,000 crore of this grain every year to spoilage, pests, pilferage, and procurement fraud. Every gram lost is food that was grown, transported, and paid for — and then wasted because nobody was watching. The five grain solutions in this domain change that. Each addresses a specific failure point in the chain from farm gate to PDS beneficiary.

GR-1 Smart Silo & Godown Monitoring

Grain Management · Year 3–4 · ECE + CSE

Dimension	Detail
Scale	150K+ Fair Price Shops, 2,300 silos, 700+ FCI depots; 80M+ tonnes stored annually
Impact	Save ₹12,000+ cr from ₹92,000 cr annual grain loss
Hardware needed	Grain probe sensor — stainless steel, multi-point temp + humidity inside grain stack; CO ₂ + ethylene sensor — fermentation/fungal detection; load cell — precision weight monitoring; acoustic pest detector; solar LoRa node — IP65 for godown dusty conditions
Software needed	Spoilage prediction ML; FCI FIMS integration; PDS alert system for FPS dealers; blockchain grain provenance; WDRA digital warehouse receipt
Why local	FCI FIMS, PDS, PMGKAY are India-specific. Indian grain varieties and climate zones require India-calibrated spoilage models
Sensor integrity note	⚠ Grain probe insertion causes physical disturbance — must be minimally invasive. CO ₂ sensor requires factory calibration + field verification against reference gas. Load cell requires certified dead weight calibration
POC entry point	ESP32 + DHT22 + CO ₂ sensor + ThingSpeak — logical check only
Engineering target	STM32U5 cluster + grain probe sensors + CO ₂ + load cell + STM32WL LoRa + IP65 + FCI FIMS API

GR-1: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
FCI FIMS	fci.gov.in	Food Corporation of India — Food Inventory Management System, stock reporting
WDRA	wdra.gov.in	Warehouse Development & Regulatory Authority — digital warehouse receipts
PDS Portal	dfpd.gov.in	Department of Food & Public Distribution — FPS stock levels, beneficiary data
PMGKAY	dfpd.gov.in/pmgkay	Pradhan Mantri Garib Kalyan Anna Yojana — free grain scheme tracking
CIPMC	cipmc.res.in	Central Integrated Pest Management Centre — pest protocols, intervention triggers

GR-1: Engineering Notes

CO₂ sensor choice — NDIR (Non-Dispersive Infrared) is mandatory for grain storage:

MH-Z19 (NDIR): ±50 ppm accuracy, factory calibrated, stable in dusty godown conditions.

MQ-135 (electrochemical): sensitive to humidity, dust, temperature — unreliable in godown.

Grain probe design: Probe must penetrate grain stack to 1–2 metre depth for accurate core temperature.

Probe material: SS304 or SS316L minimum — no galvanised, no mild steel (rust contamination).

Probe diameter: < 20mm to minimise physical disturbance during insertion.

Multi-point: 5–8 sensors per probe at different depths — grain temperature varies 3–8°C top-to-bottom.

Ethylene gas monitoring: Fungal infection produces ethylene before visible mould.

Electrochemical ethylene sensor: requires fresh air purge between readings — firmware complexity.

MOS (Metal Oxide Semiconductor) ethylene: cross-sensitive to humidity — godown conditions make this unreliable.

Best option: MiCS-5524 MOS sensor with temperature-humidity compensation firmware.

IP65 for godown: grain dust is explosive above 50 g/m³ — verify ATEX Zone 22 requirements for sites above this threshold.

GR-2 Farm-Gate Grain Quality Grading

Grain Management · Year 4 · ECE + CSE

Dimension	Detail
Scale	7,000+ APMCs, 22,000+ PACS, 585 MSP procurement districts
Impact	Farmers recover 20–30% lost income; eliminate middleman manipulation
Hardware needed	NIR spectrometer — trained on Indian grain varieties (wheat, paddy, jowar, bajra, ragi, maize); portable handheld version for FPO field agents; camera-based impurity detector; GPS-tagged sampler; ruggedised mandi kiosk
Software needed	NIR grain quality ML — India-variety specific; e-NAM integration; PM-KISAN ID linkage; digital quality certificate; MSP calculator; vernacular voice output
Why local	NIR models built for North American wheat are useless for jowar or ragi. e-NAM, MSP, APMC regulations vary by state — entirely India-specific
Sensor integrity note	⚠ NIR spectrometer requires calibration against wet chemistry reference for each grain variety. Calibration laboratory must be NABL accredited. Recalibration required seasonally as new crop varieties arrive
POC entry point	AS7265x spectral sensor + ESP32 + basic grain classification — logical check only
Engineering target	NXP i.MX8M Plus + NIR module + camera + GPS + NABL calibration + e-NAM API

GR-2: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
e-NAM	enam.gov.in	Electronic National Agriculture Market — quality-linked price, buyer-seller matching
NAFED	nafed-india.com	National Agricultural Cooperative — MSP procurement, quality standards
APEDA	apeda.gov.in	Agricultural & Processed Food Export — quality certification for export
Agmarknet	agmarknet.gov.in	Agri marketing info network — commodity grade definitions, price data
PM-KISAN	pmkisan.gov.in	Farmer ID linkage for payment trigger on quality-certified grade

GR-2: The Open Innovation Note

This is one of the most open engineering opportunities in the entire 52-solution set.

What exists today for grain grading in India:

Human visual grading — entirely subjective, manipulable by middlemen.

Imported NIR grain analysers (Perten, PerkinElmer, FOSS) — ₹15–60 lakh per unit.

No Indian NIR model trained on jowar, bajra, or ragi — globally.

What needs to exist:

A portable NIR grain grader under ₹50,000 trained on India's 100+ grain varieties.

With e-NAM API integration and vernacular voice output.

With NABL-calibrated reference dataset built in partnership with a state agriculture university.

The spectral library does not exist. The student who builds it does not just graduate.

They create the foundational dataset for every future Indian grain quality system.

That is a startup, a publication, and a government partnership in one project.

GR-3 Rodent & Pest Infestation Detection

Grain Management · Year 3–4 · ECE + CSE

Dimension	Detail
Scale	FCI loses 2M tonnes/year to rodents alone; ₹6,000 cr annual pest loss
Impact	Near-zero rodent loss with early acoustic detection; automated fumigation trigger
Hardware needed	Acoustic sensor array — ultrasonic + audible range; vibration detectors; PIR motion sensors; solar node — IP65 godown conditions; STM32N6 NPU for on-device acoustic ML
Software needed	Pest activity ML — rodent acoustic signature classification; automated fumigation trigger; FCI loss reporting integration; pest activity heatmap
Why local	Indian rodent species — Rattus rattus, Bandicota bengalensis — different acoustic signatures from European species. FCI godown construction types require India-specific sensor placement
Sensor integrity note	⚠ Acoustic sensor frequency response must be verified against calibrated reference microphone. Sensitivity drift must be monitored — dusty godown conditions degrade membranes
POC entry point	Arduino Nano 33 BLE Sense + Edge Impulse audio classification — logical check only
Engineering target	STM32N6 + acoustic array + X-CUBE-AI audio ML + LoRa + FCI API

GR-3: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
FCI	fci.gov.in	Food Corporation of India — pest loss reporting, fumigation protocol triggers
CIPMC	cipmc.res.in	Central Integrated Pest Management Centre — pest identification, treatment protocols
Edge Impulse	edgeimpulse.com	TinyML platform for acoustic rodent classification on Arduino / STM32N6
WDRA	wdra.gov.in	Warehouse receipt system — pest event logging for insurance claims

GR-3: Engineering Notes

Acoustic frequency ranges for Indian grain pests:

Rattus rattus (black rat): ultrasonic communication 20–90 kHz; scratching 100 Hz – 5 kHz

Bandicota bengalensis (bandicoot rat): larger body, lower frequency scratching 80 Hz – 3 kHz

Tribolium castaneum (flour beetle): movement sounds 200 Hz – 2 kHz — very low amplitude

MEMS microphone recommendation: SPH0645LM4H-B or ICS-43434 — flat response 100 Hz – 10 kHz.

For ultrasonic: dedicated ultrasonic transducer (MA40S4S) — 40 kHz centre frequency.

Combined array: 3× MEMS (audible) + 1× ultrasonic transducer per sensor node.

STM32N6 NPU deployment: X-CUBE-AI converts Edge Impulse .eim model to STM32-optimised C code.

Inference time target: < 200ms for 1-second audio window.

False positive rate target: < 5% (too many false alerts = fumigation cost, disruption).

False negative rate target: < 2% (missed detection = grain loss).

GR-4 PDS Supply Chain Visibility

Grain Management · Year 3 · ECE + CSE

Dimension	Detail
Scale	81 crore PDS beneficiaries; 5 lakh+ ration shops; ₹2L cr annual PDS food subsidy
Impact	Eliminate ghost beneficiaries; ensure last-mile delivery integrity; reduce ₹10,000 cr annual PDS leakage
Hardware needed	UHF RFID gates at godown exits + FPS entries; smart weighing machine — certified legal metrology; biometric PoS terminal; tamper-evident RFID grain bags; NB-IoT connectivity
Software needed	End-to-end supply chain tracker; Aadhaar-linked beneficiary authentication; state PDS portal APIs — TNPDS, UP PDS, Odisha PDS all different; PMGKAY integration; anomaly detection ML
Why local	Aadhaar authentication, state PDS systems, PMGKAY — entirely India-specific. Every state PDS portal has different API structure
Sensor integrity note	⚠ Weighing machine must carry Legal Metrology Department certification — not just calibration. Certification renewal mandatory annually under Weights & Measures Act
POC entry point	ESP32 + RFID RC522 + HX711 load cell + ThingSpeak — logical check only
Engineering target	STM32 + UHF RFID reader + legal metrology certified scale + NB-IoT + Aadhaar API

GR-4: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
PDS Portal (DFPD)	dfpd.gov.in	Central PDS dashboard, stock movement data, FPS status
TNPDS	tnpds.gov.in	Tamil Nadu PDS — beneficiary database, ration card API (state example)
UP PDS	fcs.up.gov.in	Uttar Pradesh PDS API (different structure from TN — state-specific)
PMGKAY	dfpd.gov.in/pmgkay	Pradhan Mantri Garib Kalyan Anna Yojana — free grain entitlement
UIDAI	uidai.gov.in	Aadhaar authentication API — biometric or OTP based

GR-4: Engineering Notes — Legal Metrology is Not Optional

Legal Metrology Act 2009 — Section 9: No weighing or measuring instrument shall be used in trade unless it has been verified and stamped by a Legal Metrology officer.

This means: the HX711 + load cell from an electronics supplier has NO legal standing in a trade transaction.

A PDS distribution using an uncertified scale is an illegal transaction, regardless of IoT system quality.

Legal Metrology certification process:

- 1. Select a load cell from a type-approved manufacturer (Avery Weigh-Tronix, Mettler Toledo, etc.)*
- 2. Integrate into weighing instrument per the approved type*
- 3. Submit to State Legal Metrology Officer for verification and stamping*
- 4. Annual re-verification mandatory*
- 5. Any software update affecting weight display requires re-verification*

State-by-state PDS API note:

TNPDS, UP PDS, Odisha PDS, Karnataka AePDS — all have different API structures, different authentication methods, and different data schemas.

A PDS IoT product must be built for integration flexibility — state-configurable, not hard-coded.

GR-5 MSP Grain Procurement Monitoring

Grain Management · Year 3–4 · ECE + CSE

Dimension	Detail
Scale	20M+ farmers sell at MSP centres; ₹2L cr+ annual MSP procurement
Impact	Transparent MSP payment; eliminate procurement fraud; direct DBT payment trigger
Hardware needed	Precision load cell — 24-bit ADC, legal metrology certified; GPS-tracked procurement truck; RFID-tagged grain bags; 4G modem; ruggedised field terminal
Software needed	ML procurement demand forecasting; direct DBT payment trigger on verified weight; NAFED + FCI integration; farmer PM-KISAN ID verification; state procurement agency APIs
Why local	MSP regime, procurement agencies (FCI, NAFED, state agencies), DBT payment system — entirely India-specific
Sensor integrity note	⚠ Load cell at procurement centre is a legal instrument — must carry Legal Metrology certification. Tamper evidence mandatory — any physical interference must be logged and flagged
POC entry point	Arduino + HX711 + load cell + serial monitor — logical check only
Engineering target	STM32H7 + 24-bit ADC + legal metrology certified load cell + 4G + NAFED API

GR-5: Key Government APIs & Links

API / Platform	URL	What It Enables for This Solution
NAFED	nafed-india.com	National Agricultural Cooperative — MSP procurement, grading standards
FCI Procurement	fci.gov.in	Food Corporation of India — procurement planning, depot allocation
DBT Bharat	dbtbharat.gov.in	Direct Benefit Transfer — payment trigger to farmer's bank account
PM-KISAN	pmkisan.gov.in	Farmer ID verification, bank account linkage for DBT
Agmarknet	agmarknet.gov.in	Market prices — MSP comparison, grade verification

GR-5: Engineering Notes

24-bit ADC for load cell — why precision matters in procurement:

Typical 5-tonne procurement scale: $5000 \text{ kg} / 2^{24} = 0.0003 \text{ kg}$ resolution = 0.3 gram

At MSP ₹2,183/quintal (wheat 2024): 0.3 gram error = ₹0.0007 — negligible.

BUT: a systematic 0.1% error over 1,000 tonne procurement = 1 tonne = ₹21,830 per centre per season.

Across 585 procurement districts: ₹12.75 crore/season systematic error from sensor calibration alone.

Tamper evidence design:

Load cell housing must have physical tamper seal (visible wire break on opening).

Accelerometer on weighing platform — any movement during weighing flagged in log.

GPS location must match registered procurement centre location — mismatch = alert.

All weight readings signed with device private key — cryptographic tamper evidence.

DBT payment trigger integration:

Weight verified → farmer ID verified (PM-KISAN / Aadhaar) → grade declared → payment calculated

→ DBT payment initiated via PFMS (Public Financial Management System)

→ SMS confirmation to farmer's registered mobile number

This entire chain must complete within 48 hours per NAFED/FCI guidelines.

Grain & Food Stock Domain Summary — The Five-Solution Chain

The five grain solutions form a complete chain from storage to consumer: silo monitoring (GR-1) → quality grading at farm gate (GR-2) → pest detection in storage (GR-3) → PDS supply chain (GR-4) → MSP procurement (GR-5). Each solution addresses a specific ₹6,000–₹25,000 crore annual loss that currently goes unchecked.

Solution	Year	Where in Chain	POC (Logical Check)	Engineering Target	Impact
GR-1 Smart Silo	3–4	Storage	ESP32 + DHT22 + CO ₂ + ThingSpeak	STM32U5 + grain probe + CO ₂ NDIR + load cell + LoRa + FCI FIMS	₹12,000 Cr
GR-2 Quality Grading	4	Farm gate → mandi	AS7265x + ESP32 + classification	i.MX8M Plus + NIR module + camera + NABL + e-NAM API	₹25,000 Cr
GR-3 Pest Detection	3–4	Storage	Nano 33 BLE + Edge Impulse audio	STM32N6 + acoustic array + X-CUBE-AI + LoRa + FCI API	₹6,000 Cr
GR-4 PDS Supply Chain	3	Godown → FPS → beneficiary	ESP32 + RFID + HX711 + ThingSpeak	STM32 + UHF RFID + LM certified scale + NB-IoT + Aadhaar API	₹10,000 Cr
GR-5 MSP Procurement	3–4	Farm gate → procurement centre	Arduino + HX711 + serial monitor	STM32H7 + 24-bit ADC + LM certified load cell + 4G + NAFED API	₹8,000 Cr

Shared Engineering Principles — Agriculture & Grain Domain

1. Soil and Grain Contact Sensor Materials

Sensor Type	Correct Material	Wrong Material	Failure Mode	Indian Context
Soil moisture electrodes	SS316L or titanium	Copper, brass, galvanised iron	Galvanic corrosion. Reading drifts to zero within 3–8 weeks.	Black cotton soil is alkaline — accelerates non-SS corrosion
Grain probe body	SS304 or SS316L	Mild steel, aluminium	Rust contamination in grain stack. FSSAI food safety violation.	Indian monsoon humidity accelerates rust on non-SS metals
Water quality probes (AG-5)	Platinum or graphite electrodes, SS316L housing	Uncoated copper, aluminium	Galvanic corrosion in saline coastal water within weeks.	Bay of Bengal: higher salinity than Arabian Sea — higher corrosion rate
Load cell body (GR-4, GR-5)	Aluminium alloy (bending beam) or SS (shear beam)	Any painted or coated mild steel	Paint chips contaminate grain, fail food safety inspection.	Procurement centres: dust + humidity + vibration — SS more reliable

2. AC Excitation — Mandatory for All Electrochemical Sensors

DC excitation on any electrochemical sensor causes electrolysis.

Electrolysis deposits ions on electrodes.

Electrode characteristics change. Reading drifts. Permanently.

The dashboard shows confident numbers. The numbers are wrong.

AC excitation eliminates net DC current. No electrolysis. Stable reading.

Required for: AG-1 soil moisture, AG-1 NPK, AG-3 flow meter, AG-5 pH, AG-5 DO, AG-5 conductivity

Frequency: 1–10 kHz for soil | 3 kHz for conductivity | > 1 kHz for pH (to prevent polarisation)

Implementation: STM32 DAC + op-amp generates AC excitation signal.

Reference: Decagon / METER Group soil sensor design application notes (publicly available).

3. NABL Calibration vs NABL Accreditation — The Difference That Matters

NABL ACCREDITATION: The National Accreditation Board for Testing and Calibration Laboratories accredits a laboratory to perform calibration. The lab is NABL accredited.

NABL CALIBRATION: A calibration certificate issued by a NABL accredited laboratory. The certificate is traceable to national standards (NPL India).

What students must verify for every sensor they deploy:

1. Is the calibration certificate issued by a NABL accredited laboratory?
2. Is the calibration traceable to NPL India or an equivalent national standard?
3. What is the stated uncertainty on the certificate? (e.g. $\pm 0.1^{\circ}\text{C}$, $\pm 2\%$ RH)
4. What is the calibration expiry date?
5. Is the sensor deployed within the temperature/humidity range covered by the calibration?

Without YES to all five: the data has no authority.

CPCB, FCI, ABDM — all require traceable calibration before accepting sensor data.

4. Legal Metrology — India's Most Misunderstood Certification

India's Legal Metrology Act 2009 governs all instruments used in trade.

Any weighing machine used in a commercial transaction must be:

- Type-approved by the Central Government (the instrument design is certified)
- Verified and stamped by the State Legal Metrology Officer
- Re-verified annually

This applies to: GR-4 PDS weighing terminals | GR-5 MSP procurement scales

And to any other solution involving billing by weight or volume (EN-1 smart meters, SC-1 water meters)

The HX711 load cell from an electronics shop is NOT a Legal Metrology instrument.

It is a component. It becomes a Legal Metrology instrument only after type approval and verification.

Faculty must tell students: the engineering challenge in GR-4 and GR-5 is not the sensor.

It is making the sensor comply with the legal framework that governs its use.

That is a harder and more valuable engineering skill than programming.

5. LoRa India Band — The Most Common Implementation Error

India LoRa band: 865–867 MHz (IN865)

European LoRa band: 863–870 MHz (EU868, default centre frequency 868 MHz)

Every LoRa module ships with European defaults.

If you deploy a LoRa module in India without changing the frequency: you are operating out-of-band.

This is a WPC (Wireless Planning & Coordination) regulation violation.

Fix in firmware:

```
lora.setFrequency(866000000); // 866 MHz — India IN865 band
```

```
lora.setSubBand(2); // Sub-band for India
```

Always verify with NanoVNA: transmit on 866 MHz and confirm with spectrum analyser or NanoVNA sweep.

Do not assume the firmware change is sufficient — measure it.

Cross-References

For	Go to
Hardware taxonomy for all AG and GR solutions (MCU, RF, sensors)	Appendix B: Hardware Stack Reference
PCB design rules, 4-layer requirement, EMC violations in college projects	Appendix C1: Engineering Integrity
Soil sensor material science, AC excitation, NABL calibration chain, data authority	Appendix C2: Sensor Integrity
LoRa antenna design, VSWR measurement, India band link budget	Appendix D: Antenna Engineering
BIS CRS, WPC ETA, Legal Metrology, FSSAI certification guide	Appendix E: Certification & Compliance
India semiconductor mission, PCB ecosystem, government schemes for hardware startups	Appendix F: India Hardware Ecosystem
ECE-CSE co-creation framework — how to pair students, joint assessment	Appendix G: Co-Creation Framework
Edge Impulse guide, NPTEL courses, Indian agricultural datasets, ICAR open data	Appendix H: Learning Ecosystem
Master index of all 52 solutions with year suitability and certification tiers	Appendix A6: Master Solutions Index